

NOTES — STANDARD SYSTEM BUILD-UP (TYPICAL) · SPECIFICATION SECTION 09 67 23 RESINOUS FLOORING

1. Substrate: Concrete mechanically prepared to CSP 3 or greater (ICRI 310.2R), clean, sound, and dry.
2. Fast-cure (1-day) flake system; the MavCoat FC basecoat at 16 mils total carries moisture vapor tolerance to 12 lbs./1,000 sq. ft./24 hr (ASTM F1869) per MavTop UFB System Guide.
3. Thicknesses per the referenced Maverick data sheet / system guide and the component product data sheets. Drawing not to scale.

MAVTOP UFB

STANDARD SYSTEM BUILD-UP · ISOMETRIC, EXPLODED
DWG MAV-TOP-UFB-001 · REV 1 · 10-10-2026



MAVSEAL UPA
Clear Polyaspartic Sealer · 10–16 mils

MAVCOAT FC + DECORATIVE CHIP
Fast-Cure Epoxy Basecoat with Vinyl Flake Broadcast to Rejection · 16 mils basecoat

CONCRETE SUBSTRATE
Mechanically Prepared

Dept. ENGINEERING	Technical reference MavTop UFB System Guide	Created by MAVERICK	Approved by		
<div> MAVERICK PERFORMANCE SOLUTIONS 25911 Northline Commerce Drive, Suite 306, Taylor, MI 48180 maverickperformancesolutions.com · sales@mavtechsol.com</div>		Document type SYSTEM BUILD-UP · SCALE: NTS	Document status SHOP DRAWING		
		Title MavTop UFB	DWG No. MAV-TOP-UFB-001		
			Rev. 1	Date of issue 10-10-2026	Sheet 1/1